

# 304 Series™

Parking Structure Luminaire – Mounting O – TM (Type II Medium)

## Product Description

Cree 304 Series is a highly versatile fixture which adapts to a wide range of applications: from gas station forecourt canopies, to industrial installations and tunnel lighting. The mounting system allows for extremely rapid and simple ceiling installation. Luminaire is constructed from rugged die cast and extruded aluminum components. LED driver is mounted in a sealed weathertight center chamber that allows for access from below the luminaire.

High performance aluminum heat sinks specifically designed for LED parking structure application. Mounting brackets designed to mount directly over existing flat ceilings for direct mount.

## Performance Summary

Utilizes BetaLED® Technology


Patented NanoOptic® Product Technology

**CRI:** Minimum 70 CRI

**CCT:** 5700K (+/- 500K) Standard, 4000K (+/- 300K)

**Limited Warranty†:**

10 years on luminaire / 10 years on Colorfast DeltaGuard® finish



## Ordering Information

Example: 30XTM004E43DWHI5

30	X	TM	O	04	E	43	WH	I5
Product	Insulation Class	Optic	Mounting	LED count x 10	GEN	Options	Color Options	Drive Current
30	x Class 1	TM Type II Medium	O Fixed ceiling mounting system	04 06	E	<b>no code</b> 5700K <b>43</b> 4000K Color Temperature - Color temperature per luminaire <b>D</b> 1-10V Dimming - Control by others - Refer to dimming spec sheet for availability and additional information - Can't exceed specified drive current <b>K#</b> Light Control with Occupancy Sensor - Flux dimming control with occupancy sensor <b>E</b> Light Control with Occupancy Sensor with remote control - Flux dimming control with occupancy sensor with remote control <b>N#</b> Reprogrammable Virtual Midnight - Reprogrammable 2 levels option with virtual midnight	<b>WH</b> White (Standard) <b>SV</b> Silver <b>BK</b> Black <b>BZ</b> Bronze <b>SB</b> Silver Bronze	<b>no code</b> 700mA <b>I5</b> 525 mA <b>I3</b> 350 mA

† See [www.cree-europe.com](http://www.cree-europe.com) for warranty terms



Rev. Date: 11 April 2014



[www.cree-europe.com](http://www.cree-europe.com)

Ph. +39 055 343081 Fax +39 055 34308200

## Parking Structure Luminaire – Mounting O - TM (Type II Medium)

### Product Specifications

#### CONSTRUCTION & MATERIALS

- Constructed from rugged die cast and extruded aluminum components
- LED driver is mounted in a sealed weathertight center chamber that allows for access from below the luminaire
- High performance heat sinks specifically designed for LED parking structure application
- Mounting bracket is designed to mount directly over existing flat ceilings for direct mount
- Exclusive Colorfast DeltaGuard® finish features an E-Coat epoxy primer with an ultra-durable powder topcoat, providing excellent resistance to corrosion, ultraviolet degradation and abrasion. Available colours are White, Silver, Silver Bronze, Bronze and Black

#### ELECTRICAL SYSTEM


- Input Voltage:** 220-240V, 50/60Hz
- Power Factor:** > 0.9 at full load
- Total Harmonic Distortion:** < 20% at full load
- Integral 10kV surge suppression protection standard
- To address inrush current, slow blow fuse or type C / D breaker should be used

#### REGULATORY & VOLUNTARY QUALIFICATIONS


- CE / ENEC Listed
- Enclosure rated IP66 per IEC 60529
- 10kV surge suppression protection tested in accordance with IEEE /ANSI C62.41.2
- Luminaire and finish endurance tested to withstand 5,000 hours of elevated ambient salt fog conditions as defined in ASTM Standard B 117
- RoHS Compliant

### Photometry

All published luminaire photometric testing performed to IESNA LM-79-08 standards by a NVLAP certified laboratory.



cd/klm  
 — C0 - C180 — C90 - C270 — C15 - C195



lux

**Test Report #:** CESTL-2013-0025

30XTM004E43  
**Mounting Height:** 6m  
**Initial Delivered Lumens:** 7137

#### IES Files

To obtain an IES file specific to your project, please consult [www.cree-europe.com](http://www.cree-europe.com)

### Weight

LED Count (x10)	Weight
04	8 Kg
06	

### Lumen Output, Electrical, and Lumen Maintenance Data

Effective Flux (lm) - TM (Type II Medium) Distribution						
LED Count (x10)	5700K	4000K	System Watts 220-240V	Total Current (A)	50K Hours Projected Lumen Maintenance Factor @ 15° C (59° F)	L <sub>70</sub> Life* (hours)
	Delivered Lumens	Delivered Lumens		230V		
350mA @ 25° C (77° F)					94%	>150000
04	4031	3911	46	0.21		
06	6047	5866	66	0.31		
525mA @ 25° C (77° F)					93%	149000
04	5805	5632	70	0.30		
06	8708	8448	99	0.45		
700mA @ 25° C (77° F)					91%	129000
04	7357	7137	91	0.40		
06	11036	10706	132	0.60		

\* Based on fixture operating at 25° C