LEDway® Road

IP66 Street Light – Adjustable Arm Mount – QVS (Type V Short)

Product Description

Luminaire housing is all aluminum construction. All components are mercury free and recyclable. Sharp profile for low wind exposure. Tooless entry. Provided with a tenon mounting system that allows for direct arm or pole-top installation (90°) on cylindrical poles and arms with a diameter of 60mm. The adjustable bracket allows the fixture to be tilted by increments of 5° in order to maintain a horizontal position with respect to the ground, making it ideal for retrofit installations as well.

Performance Summary

Utilizes BetaLED® Technology

Patented NanoOptic® Product Technology

CRI: Minimum 70 CRI

CCT: 5700K (+/- 500K) Standard, 4000K (+/- 300K)

Warranty†:
Class 1 - 10 years on luminaire/10 years on Colorfast DeltaGuard® finish
Class 2 - 5 years on luminaire/10 years on Colorfast DeltaGuard® finish

Accessories

Field Installed Accessories	
BRDSPK30 Bird Spikes for Light Engine, 20-30 LEDs	**KIT ADATT. PALO 34MM** Adaptor Kit for dia. 34mm poles
BRDSPK60 Bird Spikes for Light Engine, 40-60 LEDs	**KIT ADATT. PALO 42MM** Adaptor Kit for dia. 42mm poles
BRDSPK120 Bird Spikes for Light Engine, 80-120 LEDs	**KIT ADATT. PALO 48MM** Adaptor Kit for dia. 48mm poles
BRDSPKHSG Bird Spikes for Housing	

LED Count	Dimension	Measurement	Weight
20	"A"	156mm	7,52kg
30		156mm	7,92kg
40		270mm	9,22kg
50		270mm	10,42kg
60		270mm	10,52kg
80		552mm	14,72kg
90		552mm	14,82kg
100		552mm	14,92kg
110		552mm	15,02kg
120		552mm	15,12kg

Ordering Information

Example: LXDQVS702EGSVI5

L	X	D	QVS	7	02	E	G	SV	I5
Product	**Insulation Class**	**Model**	**Optic**	**Mounting**	**LED Count (x10)**	**Version**	**Options** *(consult company for available options)*	**Color Options***	**Drive Current**
LEDway	**X** Class 1 **Y** Class 2	**D** Road	**QVS** Type V Short	**7**	**02** **03** **04** **05** **06** **08** **09** **10** **11** **12**	**E**	**No code 5700K** **43 4000K** **K# Light Control with Occupancy Sensor**** - Flux dimming control with occupancy sensor **D# Power Line Communication System (PLC)** - Power line control system with dimmable driver **G# Bi-Level Control** - Two distinct power levels, High/Low **D Dimmable Driver** - Dimmable driver 1-10V with external controller **S# Virtual Midnight** - Two levels option with virtual midnight - Available up to 100 LEDs in class 1 - Available up to 60 LEDs in class 2 **T# Reprogrammable Virtual Midnight** - Reprogrammable 2 levels option with virtual midnight **R# Flux Dimming** - Integral dimming system with plants including flux regulators - Available up to 100 LEDs in class 1 - Available from 80 to 120 LEDs in class 2	**SV** Silver (Standard) **BK** Black **BZ** Bronze **SB** Silver Bronze **WH** White	**No Code** 700mA **I5** 525mA **I3** 350mA

* Light engine portion of extrusion is not painted and will remain natural aluminum regardless of color selection
† See www.cree.com/lighting for warranty terms
** Not available in Class 2

Rev. Date: 14 March 2014

www.cree-europe.com Ph. +39 055 343081 Fax +39 055 34308200

Product Specifications

BETALED® TECHNOLOGY

LEDway® Road luminaires are powered by BetaLED® Technology delivering outstanding illumination, lasting performance and optimum energy efficiency. Patented NanoOptic® technology optimizes target illumination, performance and offers flexibility with multiple optic choices. NanoOptic compliant with light pollution and photobiological safety standards

CONSTRUCTION & MATERIALS

- Housing is all aluminum construction
- Designed with 1-10V dimming capabilities. Controls by others
- Adjustable mounting arm is rugged die cast aluminum and mounts to a 60mm outer dimension tenon
- Exclusive Colorfast DeltaGuard® finish features an E-Coat epoxy primer with an ultradurable powder topcoat, providing excellent resistance to corrosion, ultraviolet degradation and abrasion. Standard is silver. Bronze, black, white, and silver bronze are also available

ELECTRICAL SYSTEM

- **Input Voltage:** 220 – 240Vac (capable 120-277Vac, please consult company for available configurations) 50/60Hz
- **Power Factor:** > 0.9 at full load
- **Total Harmonic Distortion:** < 20% at full load
- Quick disconnect harness suitable for mate and break under load provided on power feed to driver for ease of maintenance

REGULATORY & VOLUNTARY QUALIFICATIONS

- CE Listed
- ENEC Listed only for class II
- Enclosure rated IP66 per IEC 60529
- 10kV surge suppression protection tested in accordance with IEEE/ANSI C62.41.2, for Class I only
- Luminaire and finish are endurance tested to withstand 5,000 hours of elevated ambient salt fog as defined in ASTM Standard B 117
- RoHS Compliant

Photometry

All published luminaire photometric testing performed to IESNA LM-79-08 standards by a NVLAP certified laboratory.

cd/klm
C0 - C180 C90 - C270

lux

ITL Test Report #: 68092

LXDQVS704E43
Mounting Height: 6m
Initial Delivered Lumens: 9083

IES Files
To obtain an IES file specific to your project, please consult www.cree-europe.com

Effective Flux (lm) - QVS (Type V Short) Distribution

LED Count (x10)	5700K Delivered Lumens	4000K Delivered Lumens	System Watts 220–240V	Total Current (A) 230V	50K Hours Projected Lumen Maintenance Factor @ 15˚C (59˚F)	L_{70} Life* (hours)
350mA @ 25˚C (77˚F)						
02	2565	2489	25	0.13	94%	>150000
03	3848	3733	35	0.17		
04	5130	4977	46	0.21		
05	6314	6222	56	0.27		
06	7696	7466	66	0.31		
08	10261	9954	89	0.42		
09	11543	11199	99	0.46		
10	12826	12443	108	0.52		
11	14109	13687	117	0.58		
12	15391	14932	126	0.62		
525mA @ 25˚C (77˚F)						
02	3694	3584	37	0.17	93%	149000
03	5541	5375	52	0.24		
04	7388	7167	70	0.30		
05	9235	8959	86	0.39		
06	11082	10751	99	0.45		
08	14775	14334	141	0.59		
09	16622	16126	157	0.65		
10	18469	17918	172	0.74		
11	20316	19710	187	0.83		
12	22163	21502	203	0.89		
700mA @ 25˚C (77˚F)						
02	4681	4542	49	0.23	91%	129000
03	7022	6813	70	0.32		
04	9363	9083	91	0.40		
05	11704	11354	112	0.52		
06	14044	13625	132	0.60		
08	18726	18167	183	0.79		
09	21067	20438	203	0.86		
10	23407	22709	224	1.02		
11	25748	24979	243	1.12		
12	28089	27250	264	1.26		

* Based on fixture operating at 25° C

Maximum Wind Area
(lateral surface exposed to wind):

LED Count (x10)	Arm Mount	Pole Top Mount
02 03	0.051 m2	0.061 m2
04 05 06	0.060 m2	0.070 m2
08 09 10 11 12	0.080 m2	0.090 m2

© 2014 Cree, Inc. and/or one of its subsidiaries. All rights reserved. For informational purposes only. Content subject to change. See www.cree.com/patents for patents that cover these products. Cree®, the Cree logo, BetaLED®, NanoOptic®, and Colorfast DeltaGuard® are registered trademarks, and the BetaLED Technology logo, Precision Delivery Grid™ and LEDway® are trademarks of Cree, Inc. or one of its subsidiaries.

www.cree-europe.com Ph. +39 055 343081 Fax +39 055 34308200